

## Apparel Folding Equipments & Automation

# Bag<sup>X</sup>basic



**Bag<sup>X</sup>basic** is a semi automatic L-Sealer.

The operator will feed the apparel into position and manually close to seal.

**BagX<sup>basic</sup>** LS-16 L-Sealer is a heavy duty production based unit designed to be run 2 shifts per day if needed. With its heavy duty frame construction, cast aluminum seal head and Hot Knife Seal Technology, you will get years of use with minimal repairs. This machine is capable of operating at speeds of around 600 – 800 pieces/ hr.

## Standard Features include:

- Hot Knife- Teflon Coated Steel Blades
- Motorized Discharge Conveyor
- Seal & Magnet Timer
- Seal Heat Return Cylinder
- Dual Magnet Hold Down
- Stainless Steel Film Clamps
- Pin Wheel Hole Punch
- Discharge Conveyor Timer
- Locking Casters
- Powder Coated Frame
- Transition Rollers on Discharge Conveyor
- Film Roll Guides
- Constant Heat for Sealing
- Film Roll Brake to prevent over-winding
- Heavy Duty Frame Construction
- Independent Front and Side Digital Temperature Controls.

## Specifications:

**Power:** 220 Volt, 1 Phase, 15 AMPS

**Weight:** 325 lb net/ 380 shipping

**Seal Dimensions:** L 22" x W 16"

**Max Film Width:** 20"

**Machine Dimensions:** L 64" x W 27" x H 39"



## **Contact:**

**DEKKEN USA, INC**

**805 Essex Drive**

**Summerville, SC 29485**

**Ph.: 843.708.8444**

**e-mail: [info@dekkenusa.com](mailto:info@dekkenusa.com)**

**Web: <https://dekkenusa.com/>**